

Daya Bay Reactor Neutrino Experiment

Jun Cao

On behalf of the Daya Bay Collaboration

caoj@ihep.ac.cn

Institute of High Energy Physics

XIII International Workshop on Neutrino Telescopes, Venezia, Mar. 10-13, 2009

Neutrino Oscillation


Neutrino Mixing: PMNS Matrix

$$\begin{pmatrix} 1 & 0 & 0 \\ 0 & \cos \theta_{23} & \sin \theta_{23} \\ 0 & -\sin \theta_{23} & \cos \theta_{23} \end{pmatrix} \begin{pmatrix} \cos \theta_{13} & 0 & e^{-i\delta} \sin \theta_{13} \\ 0 & 1 & 0 \\ -e^{i\delta} \sin \theta_{13} & 0 & \cos \theta_{13} \end{pmatrix} \begin{pmatrix} \cos \theta_{12} & \sin \theta_{12} & 0 \\ -\sin \theta_{12} & \cos \theta_{12} & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

Atmospheric,
K2K, MINOS, T2K, etc.
 $\theta_{23} \sim 45^\circ$

Reactor
Accelerator
 $\theta_{13} < 12^\circ$


Solar
KamLAND
 $\theta_{12} \sim 30^\circ$



Known: $|\Delta m_{32}^2|$, $\sin^2 2\theta_{23}$, Δm_{21}^2 , $\sin^2 2\theta_{12}$

Unknown: $\sin^2 2\theta_{13}$, δ_{CP} , Sign of Δm_{32}^2

Measuring θ_{13} at reactors




Reactor ($\bar{\nu}_e$ disappearance)

Clean in physics, only related to θ_{13}

Cheaper and faster

$$P_{ee} \approx 1 - \sin^2 2\theta_{13} \sin^2 \left(\frac{\Delta m_{31}^2 L}{4E_\nu} \right) - \cos^4 \theta_{13} \sin^2 2\theta_{12} \sin^2 \left(\frac{\Delta m_{21}^2 L}{4E_\nu} \right)$$




Accelerator (ν_e appearance)


Related to CP phase, θ_{13} , and mass hierarchy

$$\begin{aligned} P(\nu_\mu \rightarrow \nu_e) = & 4c_{13}^2 s_{13}^2 s_{23}^2 \sin^2 \Delta_{31} \\ & + 8c_{13}^2 s_{13} s_{23} c_{23} s_{12} c_{12} \sin \Delta_{31} [\cos \Delta_{32} \cos \delta - \sin \Delta_{32} \sin \delta] \sin \Delta_{21} \\ & - 8c_{13}^2 s_{13}^2 s_{23}^2 s_{12}^2 \cos \Delta_{32} \sin \Delta_{31} \sin \Delta_{21} \\ & + 4c_{13}^2 s_{12}^2 [c_{12}^2 c_{23}^2 + s_{12}^2 s_{23}^2 s_{13}^2 - 2c_{12} c_{23} s_{12} s_{23} s_{13} \cos \delta] \sin^2 \Delta_{21} \\ & - 8c_{13}^2 s_{13}^2 s_{23}^2 (1 - 2s_{12}^2) \frac{aL}{4E_\nu} \sin \Delta_{31} \left[\cos \Delta_{32} - \frac{\sin \Delta_{31}}{\Delta_{31}} \right]. \end{aligned}$$

Proposals for measuring θ_{13} at reactors



Measuring $\sin^2 2\theta_{13}$ to 0.01



Planned Exp.





If $\sin^2 2\theta_{13} < 0.01$, long baseline (LBL) experiments with conventional beam have little chance to determine the CP violation.

Measuring $\sin^2 2\theta_{13}$ to 0.01 will provide a roadmap for the future LBL experiments.

“We recommend, as a high priority, ..., An expeditiously deployed multi-detector reactor experiment with sensitivity to ν_e disappearance down to $\sin^2 2\theta_{13} = 0.01$ ”

---- APS Neutrino Study, 2004

Signal and Backgrounds in detector



How to measure $\sin^2 2\theta_{13}$ to 0.01


CHOOZ: $R=1.01 \pm 2.8\%(\text{stat}) \pm 2.7\%(\text{syst})$, $\sin^2 2\theta_{13} < 0.17$

Higher statistics

- ◆ 40 ton-GW \rightarrow 1400 ton-GW at Daya Bay
- ◆ Statistical error 0.2% in 3 years.

Lessons from past experience:


- ◆ Need near and far detectors
- ◆ Chooz: Good Gd-LS
- ◆ Palo Verde: Go deeper, good muon system
- ◆ KamLAND: No fiducial cut, lower threshold



Parameter	Error	Daya Bay, Relative measurement
Reaction cross section	1.9 %	Cancel out, Near/far
Number of protons	0.8 %	Reduced to <0.3%, filling tank with load cell
Detection efficiency	1.5 %	Reduced to ~0.2%, 3-layer detector
Reactor power	0.7 %	Reduced to ~0.1%, Near/far
Energy released per fission	0.6 %	Cancel out, Near/far
Chooz Combined	2.7 %	



Sensitivity of Daya Bay

Goal: $\sin^2 2\theta_{13} < 0.01$




- Use rate and spectral shape
- input relative detector syst. error of 0.38%/detector

90% confidence level




Redundancy

- ◆ Measuring $\sin^2 2\theta_{13}$ to 0.01 need to control systematic errors very well.
- ◆ We believe that the relative (near/far) detector systematic error could be lowered to 0.38%, with near/far cancellation and improved detector design.
- ◆ **Side-by-side calibration:** Event rates and spectra in two detectors at the same near site can be compared → How IDENTICAL our detectors are?
- ◆ **Detector swapping:** Daya Bay antineutrino detectors are designed to be MOVABLE. All detectors are assembled and filled with liquids at the same place. Detectors at the near sites and the far site can be swapped, although not necessary to reach our designed sensitivity, to cross check the sensitivity and further reduce the systematic errors.



The Daya Bay Collaboration

Political Map of the World, June 1999



Europe (3) (9)

JINR, Dubna, Russia

Kurchatov Institute, Russia

Charles University, Czech Republic

North America (15)(~83)

BNL, Caltech, Cincinnati, George Mason Univ.,

LBNL, Iowa State Univ., Illinois Inst. Tech.,

Princeton, RPI, UC-Berkeley, UCLA,

Univ. of Houston, Univ. of Wisconsin,

Virginia Tech.,

Univ. of Illinois-Urbana-Champaign

Asia (18) (~126)

IHEP, Beijing Normal Univ., Chengdu Univ.

of Sci. and Tech., CGNPG, CIAE, Dongguan

Polytech. Univ., Nanjing Univ., Nankai Univ.,

Shandong Univ., Shenzhen Univ.,

Tsinghua Univ., USTC, Zhongshan Univ.,

Univ. of Hong Kong,

Chinese Univ. of Hong Kong,

National Taiwan Univ., National Chiao Tung

Univ., National United Univ.

~ 218 collaborators

The Daya Bay site




- ◆ Transportation convenient.
60 km to Hong Kong,
50 km to Shen Zhen.
A seaport in the Power Plant.
- ◆ Adjacent to high hill, ideal for underground labs.
- ◆ In the future ...
1000m high mountains at ~60km distance. Possibly to launch a intermediate-baseline experiment for mass hierarchy and precision θ_{12} measurements.
Phys.Rev.D78:111103,2008,
[arXiv:0807.3203];
[arXiv:0901.2976]

12

Daya Bay and Ling Ao Nuclear Power Plant



Goal: $\sin^2 2\theta_{13} < 0.01$ @ 90% CL in 3 years. Site: Shen Zhen, China



Power Plant

4 cores 11.6 GW
6 cores 17.4 GW from 2011

Three experimental halls

Multiple detectors at each site
Side-by-side calibration

Horizontal Tunnel

Total length 3200 m

Movable Detector


All detectors filled at the filling hall, w/ the same batch of Gd-LS, w/ a reference tank

Event Rate:



~1200/day Near
~350/day Far

Backgrounds

B/S ~0.4% Near
B/S ~0.2% Far



Daya Bay Detectors





Antineutrino Detectors

◆ Three-zone cylindrical detector design

- ⇒ Target: 20 t (0.1% Gd LAB-based LS)
- ⇒ Gamma catcher: 20 t (LAB-based LS)
- ⇒ Buffer : 40 t (mineral oil)

◆ Low-background 8" PMT: 192




◆ Reflectors at top and bottom




2-zone Prototype at IHEP

- 0.5 ton unloaded LS
- 45 8" PMTs with reflecting top and bottom

Phase-I, started in 2006,
ended in Jan. 2007



Kam-Biu Luk



Daya Bay


IHEP Prototype filled with 0.1% Gd-LS

Gd-TMHA complex synthesis




Phase-II, filled with half-ton 0.1% Gd-LS, started in Jan. 2007 and keep running until now.

The prototype is also used for the FEE and Trigger boards testing.



Stainless Steel Tank Fabrication



Acrylic Vessels




4-m AV in US



3-m AV in Taiwan

Reflective Panels




Stick the ESR® high reflectivity film on to the acrylic panel

Lifting structure testing



- ◆ Daya Bay experiment will use 200 ton normal liquid scintillator and 200 ton 0.1% gadolinium-loaded liquid scintillator (Gd-LS) .
Gd-TMHA + LAB + 3g/L PPO + 15mg/L bis-MSB
- ◆ The stability of the Gd-LS has been tested for two years with IHEP prototype detector (half ton Gd-LS) and high temperature aging tests in lab.
- ◆ All Gd-LS will be produced as one batch on-site, to ensure IDENTICAL detectors. The mixing equipment has been tested at IHEP and will be re-assembled on-site.
- ◆ 4-ton production is going on.




5000-L Acrylic
Vessel


500-L Acrylic
Vessel

Two 1000-L
Acrylic Vessels


2008 12 7



Muon System



- ◆ 2.5m thick water shielding to AD in all directions.
- ◆ Two-layer water cherenkov
 - ⇒ Cross check
 - ⇒ Measuring fast-neutron backgrounds
- ◆ Covered w/ 4-layer RPC on top.
- ◆ The combined muon efficiency ~ 99.5%.



RPC Assembly






RPC module delivering table,
which can lift the module to
the height on module rack.
Gas system is behind the
module rack.



Calibration System

- Assembly at Caltech
- Ge-68, Co-60, n, LED



Civil Construction


Control Room



Entrance




Large clean room allows two AD assembly



Surface Assembly Building




Civil Construction



Tentative Schedule

- ◆ October 2007, Ground Breaking
- ◆ March 2009, Surface Assembly Building Occupancy
 - ⇒ Antineutrino detector (AD) test assembly
- ◆ Summer 2009, Daya Bay Near Hall Occupancy
- ◆ Fall 2009, the first AD complete, Dry-run test starts
- ◆ Summer 2010, Daya Bay Near Hall Ready for Data
- ◆ Summer 2011, Far Hall Ready for Data

- ◆ Three years' data taking reach full sensitivity.



Thanks!